FLOOR-STANDING CABINETS 19″

SN-NO
Light-Duty series
Floor-Standing Data Cabinet, 19″

Door options: Glass | Perforated | Metal

SN-NO is a floor-standing cabinet for 19-inch network and telecommunications equipment. It is supplied flat-packed for self-assembly. Current configurations cover 18–42U, widths of 600/800 mm and depths of 600/800/1000/1200 mm, depending on the selected model, with a distributed static load of up to 500 kg.

Product family	SN-NO
Category	Floor-Standing Cabinet
Installation	Indoor
Rack standard	19″
Assembly	Flat-Pack



18–42 U HEIGHT

600 / 800 mm WIDTH

600 / 800 / 1000 / 1200 mm DEPTH

500 kg STATIC LOAD

IP20 PROTECTION

1 Key Features

Steel Construction
Full cold-rolled sheet-steel body construction

Glass / Perforated / Metal Door
Front door swing-handle lock, rear door cam lock

Ventilation Openings
Slotted grille along the roof edge

Cable Entry Points
Top and bottom panels

19″ Mounting Rails
2 pairs, adjustable depth, 25 mm step

Grounding
All removable parts earthed

Fan Mounting Positions
Mounting holes on a 105 × 105 mm pattern in the roof for four 120 × 120 mm fans or for a Roof Fan Unit

Access From All Sides
Front, rear and both sides open

TYPICAL APPLICATIONS

- Server Rooms
- Telecommunications Rooms
- Network Distribution Points
- Equipment Rooms
- IT Infrastructure
- Building Distribution Rooms
- LAN / WAN Infrastructure

WHAT'S IN THE BOX

- Roof and base panels
- Front and rear frames
- Two removable side panels
- Front door and rear door
- 19″ mounting rails
- Mounting rail support brackets
- 4 key sets — one set for each lock
- Set of levelling feet

COMPATIBLE ACCESSORIES



SNV Series Roof Fan Unit | Cable organizer | Plinth base

CE | IP20 | EN 62208 | 2014/35/EU


Powered by SteelNet

2 Size & Configuration Matrix


Height	Width × external depth (mm)					
	600 × 600 mm	600 × 800 mm	600 × 1000 mm	800 × 800 mm	800 × 1000 mm	800 × 1200 mm
18U 931 mm	**450** 48.6 kg	**650** 56.0 kg	—	—	—	—
20U 1020 mm	**450** 51.7 kg	**650** 59.6 kg	—	—	—	—
22U 1109 mm	**450** 54.8 kg	**650** 62.6 kg	—	—	—	—
25U 1242 mm	**450** 60.1 kg	**650** 68.5 kg	—	—	—	—
27U 1332 mm	**450** 62.9 kg	**650** 72 kg	—	—	—	—
32U 1555 mm	**450** 72.6 kg	**650** 82.3 kg	—	—	—	—
35U 1689 mm	**450** 76.8 kg	**650** 86.4 kg	—	—	—	—
42U 2000 mm	**450** 88.3 kg	**650** 98.4 kg	**850** 110 kg	**650** 111.9 kg	**850** 123.5 kg	**1050** 134.1 kg

Usable internal depth is the external depth less 150 mm. Weights are for the glass-door (GD) configuration; perforated (PD) and metal (MD) front doors vary slightly — contact DeepNet Europe for exact figures. 800 mm width is only offered at the 42U size; every other height is 600 mm wide.


3 Technical Drawing



FRONT VIEW




SIDE VIEW



TOP VIEW

Front and side views are generic for the whole range. Top view: 390 × 50 mm cable cutout mirrored on the base; 105 × 105 mm pattern for 4 fans; 420 × 250 mm pattern for the Roof Fan Unit.



EXPLODED ASSEMBLY VIEW · DOOR OPTIONS: GLASS / PERFORATED / METAL

4 Standards & Certification

- ✓ **IEC 60297-1 / -2** — 19-inch rack dimensions
- ✓ **EN 62208** — Empty LV switchgear enclosures
- ✓ **EN 60529** — Degrees of protection (IP Code)
- ✓ **2014/35/EU** — Low Voltage Directive (LVD)

5 Colour & Ordering

RAL 7035 Light grey

RAL 9005 Jet black

ORDERING CODE PATTERN

`SN-NO-FS-UA-19-[H]U-[W]-[D]-[DOOR]-MD-2SP-[RAL]`

SN-NO Series name · **FS** Floor-standing · **UA** Unassembled (flat-pack) · **19** 19-inch rack standard · **MD** Metal rear door · **2SP** Two solid side panels

`[H]`	Height in rack units: 18, 20, 22, 25, 27, 32, 35, 42	`[D]`	Depth code in metres without the decimal point: 06, 08, 10, 12
`[W]`	Width code — 06 means 600 mm, 08 means 800 mm (800 mm only at 42U): 06, 08	`[DOOR]`	Front door — GD glass, PD perforated metal, MD metal
		`[RAL]`	Powder-coat colour — 7035 light grey or 9005 black

EXAMPLE `SN-NO-FS-UA-19-27U-06-08-GD-MD-2SP-7035`

= 27 rack units high, 600 mm wide, 800 mm deep, glass front door, metal rear door, two side panels, RAL 7035 light grey.

Rear door (MD) and side panel count (2SP) are fixed and not part of the order code choice. Perforated and solid-metal front doors are catalogued options but do not yet have separate SKU rows in the price list — contact DeepNet Europe for current SKU and colour availability per size.

ul. Szczecińska 16 G, 05-300 Mińsk Mazowiecki, Poland
info@deepnet.pl · deepneteu.app